

# QS46

# 46" Quadsplit Monitor

Large Format Monitors



Large scale monitoring with broadcast quality



The Quadsplit series monitors can display 4 of its ten inputs simultaneously. The users can select from the front panel which signal is displayed in each window. There is also a full screen mode available



By default, the monitor is provided with 2 DVI-I inputs (YPbPr, VGA and DVI video modes) and 8 multiformat video inputs (for PAL/NTSC/SECAM composite video and SD-SDI signals)



The HD option in the multiformat inputs can be included at the time of purchase or activated by password at any moment afterwards and within seconds



The dynamic in-monitor displays (IMD) and tallies, both under serial protocol, allow the correct identification of each signal in real time



The analogue audio inputs and the SDI audio de-embedder can be monitored by using either the on-screen audio bars or the built-in speaker

## MAIN FEATURES

- 1920x1080 resolution
- 2 DVI-I inputs
- 8 Composite/SD/HD-SDI inputs
- HD upgrade by password activation
- Dynamic In-monitor display (serial protocol)
- Tri-colour tally (serial protocol, contact closure and voltage)
- 2 analogue audio inputs
- Audio de-embedder
- Audio bars (4 stereo channels per signal)
- Built-in speaker
- Headphone front output
- Time code display
- Remote control


## FRONT AND REAR VIEWS



## REAR INPUTS



## ACCESSORIES



## SPECIFICATIONS

LCD Panel	
Size	46" (16:9 native)
Resolution	1920x1080
Active Area	1018 x 572 mm
Viewing Angle	178° H/V
MTTF	50,000 Hours
Brightness	500 cd/m <sup>2</sup>
Contrast	4000:1
Response Time	6.5 ms
Inputs	
DVI-I	Connector: 2xDVI-I YPbPr: 1080i (60, 59.95, 50), 576e@50i, 480e@60i RGB (VGA): 640x480, 800x600, 1024x768, 1280x1024, 1600x1200 DVI Graphic Mode: 640x480, 800x600, 1024x768, 1280x1024, 1920x1080 DVI Video Mode: 1920x1080(50i, 60i, 50p, 60p)
CVS/SDI/HD-SDI	Connector: 8xBNC (autosensing) PAL/NTSC/SECAM: 576i@50, 480i@60 720p(60/59.94/50) 1080p(30/29.97/25/24/23.98), 1080i(60/59.94/50) 1035i(60/59.94)
Audio	4 stereo channels (SUB-D26 connector) SDI Embedded audio
In-Monitor Display (IMD)	RJ-45
Tally	SUB-D26 connector
GPIO	SUB-D26 connector
LTC	SDI embedded (digital) Phoenix connector (analogue)
Remote Control	Ethernet
Service	USB Type B
Outputs	
Audio	VU-meters Built-in speaker
Tally	On-screen
In-Monitor display	RJ-45 connector
General	
Dimensions	649 x 1090 x 100 mm
Weight	31 Kg
Power	Internal PSU 100-240 VAC
Operating Temperature	15-40° to meet specs
Relative Humidity	10-90% non condensing at 40°C
Ordering Info	
Model number	QS46
Input activations	QS46: HD activation for 8 SDI inputs MS1200X50: wall mounting kit MS2302X50: desktop adaptor
Accessories	