



EUROCASTER DDS 600 – 600W FM TRANSMITTER COMPACT



Prognostic

Analysis for predictive maintenance

Simply

Hot pluggable PSU - Easy to replace fans

Controls

LCD display, Web server and SNMP

Integrated unique features

Micro SD card slot

FM, Satellite and Terrestrial receiver

Advanced Efficiency Boost

Efficiency up to 75% with adaptive optimization

Digital Processing

Unique performances thanks to DDS digital modulator

Stereo & Soft clipper

Always included

Audio processor

Full telemetry with 3G connection

GENERAL SPECIFICATION

Output frequency range	Output frequency range	87.5 to 108MHz in 1Hz steps
Output Power	Output Power	600W (tol. +0/-0.5dB)
Output connector	Output connector	7-16 connector
Spurious and harmonic suppression	Spurious and harmonic suppression	Compliant with ETSI and FCC specifications
Analog input	Analog input	2x XLR female (Balanced; impedance 600Ω/10KΩ > XLR female) (Balanced; impedance 600Ω/10KΩ > XLR female)
MPX/SCA/RDS input	MPX/SCA/RDS input	2x BNC female (Unbalanced; impedance 50Ω/10KΩ > BNC female) (Unbalanced; impedance 50Ω/10KΩ > BNC female)
Soft Clipper with band limitation	Soft Clipper with band limitation	Included
Power consumption	Power consumption	Typ. 0.95KVA - Max. <1KVA
AEB (Advanced Efficiency Boost)	AEB (Advanced Efficiency Boost)	Included
Power supply	Power supply	230Vac single phase
Operative temperature	Operative temperature	-5°C to +45°C @MSL
Maximum operative altitude	Maximum operative altitude	3000m ASL For higher altitudes please contact us for higher altitudes please contact us for higher altitudes please
Maximum operative humidity	Maximum operative humidity	95% non-condensing
Housing	Housing	Rack drawer 19" 3U
Weight	Weight	<18Kg



Picture shows with optional 2nd power supply.

SOFTWARE OPTIONS

S-AM-UN	Audio monitor for input or on-air signal + test tone generator
S-SD-UN	Micro SD card slot
S-AES-UN	Digital AES/EBU & AES192 (MPX over AES) inputs
S-FMRX-UN	FM receiver input (for regenerative FM repeater/ translator)
S-SWI-UN	Automatic input switching (n.3 MPX profiles – audio/ RDS)
S-RDS-UN	Static RDS coder
S-RDS+-UN	Dynamic RDS
S-IP-UN	IP input (Icecast2 streaming & AES67)
S-DMPX-UN	Digital MPX over TS & Digital MPX over IP
S-ISO-UN	SFN/ Isosfrequency operation
S-AP-DEL	Delossifier (for audio processor H-AP-PRO)
S-AP-ARDS	Advanced RDS (for audio processor H-AP-PRO)

Included in
S-PLUS-UN

HARDWARE OPTIONS

H-SATDTT	Embedded Satellite and Terrestrial receiver demodulator. DVB-S/S2 (L-band input) and/or DVB-T/T2 and ISDB-T (VHF/UHF band input)
H-3G	2G/3G modem router for remote connection/telemetry and SMS
H-I/O	Analog telemetry interface with n.3 isolated clean contact outputs, n.4 optoisolated inputs, n.4 analog outputs (0 to 5V), mini UPS for remote control, for router and for telemetry interface, RF filter for router
H-AP-PRO	Audio Processor card with professional software license, Advanced Dynamics (Auto EQ & dynamic ratios), Declipper & Natural Dynamics
H-SATDTT2	Second Redundant Embedded Satellite and Terrestrial receiver demodulator with seamless switching
H-CAM	CAM Slot (Common Interface Module)
H-ASI	ASI T.S. input (or output) interface
H-REF	10MHz and 1pps inputs
H-GNS	High stability reference oscillator GNSS (GPS + GLONASS) locked, oven clock 10MHz + 1pps outputs
H-AGNS	GPS/GLONASS receiving antenna (gain 26dB typ.) + 15 meters cable

EuroCaster

The software-based audio processor can be integrated in any of our EuroCaster DDS transmitters, from low and medium compact versions to high power line.

“H-AP” Audio Processor offers outstanding audio quality and comes with many unique features.



FM Composite Clipper

Up to 140% audio level at 100% modulation gives 2-3 dB extra headroom for highs. Improve your audio, being the loudest and cleanest station on the dial!

Stereo & RDS Coder

Built-in stereo and RDS encoder
RT+

Advanced Dynamics & EQ

Increases the dynamics for music that lacks dynamics. Adjusts the spectrum without compression, making it possible to generate a very consistent sound without sounding compressed

Dehummer

Improves the sound of MPEG2/MP3 style lossy compressed files, removing unwanted constant sounds, such as a 50/60 Hz hum from bad cables

Better FM reception

Improves stereo reception area up to 30Km

Declipper & Natural Dynamics

Repairs clipped audio, removes distortion
Restores Natural Dynamics

Delossifier *

Improves the sound quality of MPEG2/ MP3 style lossy compressed files

All specifications contained in this document may be changed without prior notice