

4K/HD KEYER DSK-400



The DSK-400 is a 4K (UHD) keyer with 12 inputs and 8 outputs for 3G-SDI. Add DSK-400CK for 4K chroma keying. Connect to an HVS-100 for control via HVS-100OU. Also controllable via dedicated GUI.

- 1080p/1080i supported
- 3G-SDI Level-A input and Level-B (only for FILL/KEY) input supported
- Supported inputs: LINE (3G/HD-SDI x4), FILL/KEY (3G/HD-SDI x4 each)
 - 4K mode: LINE x1, FILL/KEY x1 each
 - HD (3G/1.5G) mode: LINE x4, FILL/KEY x4 each
- Supported outputs: PGM (SDI x4), AUX (SDI x4)
 - 4K mode: PGM x1, AUX x1
 - HD (3G/1.5G) mode: PGM x4, AUX x4
- Enables combined FILL/KEYs on LINE input. Equipped with FS on FILL/KEY input
- Equipped with INPUT STILL on FILL/KEY input. Available as still image source
- BOX mix, KEY INVERT, GAIN, TRANSPARENCY function
- Offers 1080p down-converted output from 4K for monitoring use
- Supports Genlock, BB or Tri-level Sync. Line lock supported for LINE input
- Bypass output supported as standard
- Built-in web server allows individual settings to be configured over web browser
- GPI input/tally output, with 16 pins assignable to input or output
- Remote control via RS-422 port available
- Simultaneous control from up to four DSK-RU, optional remote control unit
- 4K high-performance DSK-400CK chroma keyer (Option)
- Redundant DSK-400PSM power supply (Option)

4K keying



When using as 4K chroma keyer with optional DSK-400CK





Specifications

Video format	3G-SDI: 1080/59.94p, 1080/50p, HD-SDI: 1080/59.94i, 1080/50i
Processing	4:2:2:4, Digital component 10-bit
Quantization	Y: 10-bit, C: 10-bit, KEY: 10-bit
Video input	
BKGD (LINE)	3G-SDI: 3 Gbps (Level-A), HD-SDI: 1.5 Gbps, 75Ω, BNC x4
FILL	3G-SDI: 3 Gbps (Level-A/B), HD-SDI: 1.5 Gbps, 75Ω, BNC x4 (w/ built-in FS function)
KEY	3G-SDI: 3 Gbps (Level-A/B), HD-SDI: 1.5 Gbps, 75Ω, BNC x4 (w/ built-in FS function)
Reference Input	BB: NTSC: 0.429 Vp-p / PAL: 0.45 Vp-p or Tri-level Sync: 0.6 Vp-p, 75Ω BNC x 1, loopthrough (terminated w/ 75Ω terminator if unused)
Video Output	
PGM (LINE)	3G-SDI: 3 Gbps (Level-A), HD-SDI: 1.5 Gbps, 75Ω, BNC x4 (Bypass function available when powered OFF)
AUX	3G-SDI: 3 Gbps (Level-A), HD-SDI: 1.5 Gbps, 75Ω, BNC x4
I/O Delay	
Min. LINE	Approx. 6 μs (HD) / Approx. 3 μs (3G, UHD)
Min. FILL/KEY	Approx. 6 μs (HD) / Approx. 3 μs (3G, UHD)
If FS used	0 to 1 frame plus minimum delay
Video Mixing	
Keying	External KEY / Self KEY / Full KEY selectable
KEY: CLIP/GAIN/ TRANSPARENCY	Level-adjustable
FILL source	FILL input / MATTE selectable
KEY source	KEY video input for external keys
FILL MAT	Hue/saturation/luminance (color adjustment)
Edge Effect	Off/Soft/Hard selectable, Edge width 1H to 8H, Position: max. ±4 lines, Edge color adjustable
Box Mask	Top/Bottom/Left/Right/Mirror settings available
Transition	Cut or Fade in/out, remote control available
Interface	
REMOTE	15-pin D-sub (female) x1
GPI-IN/GPI-OUT/ ALARM	25-pin D-sub (female) x1 (16-input/output)
RS-422	9-pin D-sub (female) x1
LAN	10/100BASE-TX, RJ-45 x 1
Temperature / Humidity	0°C to 40°C / 10% to 90% (no condensation)
Power	100 V AC to 240 V AC ±10%, 50/60 Hz
Consumption	100 V AC to 120 V AC: 105 W, 200 V AC to 240 V AC: 109 W
Dimensions / Weight	430 (W) x 425 (D) x 44 (H) mm / 6.2 kg as standard, 6.6 kg with full option
Accessories	AC cable (w/ retaining clip), Rack mount brackets, Cable for DSK-RU connection, Operation manual (CD-ROM), Quick Setup Guide
Consumables (if used 24 hours a day at room temperature)	Power supply unit: Replace every 5 years DSK-400PSM: Replaced every 5 years Cooling fan: Replace every 4 years
Options	DSK-400CK: Chromakey expansion software, DSK-RU: Remote control unit, DSK-400PSM: Redundant power supply

Rear Panel

Unit: mm

**External Dimensions**
FOR-A
 INNOVATIONS IN VIDEO
 and AUDIO TECHNOLOGY

Head Office: 3-8-1 Ebisu, Shibuya-ku, Tokyo 150-0013, Japan

 ISO 9001 and 14001 certified
 (Sakura R&D)

<http://www.for-a.com/>

FOR-A Corporation of America: Tel: +1-714-894-3311
 11155 Knott Ave. Suite G&H, Cypress, CA 90630, U.S.A.

FOR-A Corporation of America East Coast Office: Tel: +1-201-944-1120
 2 Executive Drive, Suite 670, Fort Lee Executive Park, Fort Lee, NJ 07024, U.S.A.

FOR-A Corporation of America Distribution & Service Center: Tel: +1-352-371-1505
 2400 N.E. Waldo Road, Gainesville, FL 32609, U.S.A.

FOR-A Corporation of America Miami Office: Tel: +1-305-931-1700
 5200 Blue Lagoon Drive, Suite 760, Miami, FL 33126, U.S.A.

FOR-A Corporation of Canada: Tel: +1-416-977-0343
 1131A, Leslie Street #209, Toronto, Ontario, M3C 3L8, CANADA

FOR-A Europe S.r.l.: Tel: +39-039-879-778
 Via Volturno, 37, 20861 Brugherio MB, Italy

FOR-A UK Limited: Tel: +44-(0)20-3044-2935
 Trident Court, 1 Oakcroft Road, Chessington, KT9 1BD, UK

FOR-A Italia S.r.l.: Tel: +39-039-881-086/103
 Via Volturno, 37, 20861, Brugherio MB, Italy

FOR-A Corporation of Korea: Tel: +82-(0)2-2637-0761
 1007, 57-5, Yangsan-ro, Yeongdeungpo-gu, Seoul 150-103, Korea

FOR-A China Limited: Tel: +86-(0)10-8721-6023
 708B Huateng Building, No. 302, 3 District, Jinsong, Chaoyang, Beijing 100021, China

FOR-A Middle East-Africa Office: Tel: +971-(0)4-551-5830
 Dubai Media City, Aurora Tower, Office 1407, P.O. Box 502688, Dubai, UAE

Agiv (India) Private Limited (FOR-A India): Tel: +91-22-2405-1258
 2nd Floor, Valecha Chambers, Link Road, Andheri (W), Mumbai 400053